



■ **SAFE WORKING PRESSURE 800 BAR (11,603 PSI)**

- Tested to withstand accidental passes over the metatarsal area when using high pressure water jetting guns (up to 800 bar).
- Resistant to oils, petrol, greases, dilute acids & alkalis.
- Sanitised, washable nylon lining.
- Arch Support.
- Smooth dirt-repelling surface.
- Manufactured from heavy duty PVC for strength and longer wear life.
- 200 Joules steel toe-cap.
- Slip-resistant sole.
- Energy-absorbing heel.
- Shin guard specially reinforced.
- Strong ankle protection.
- Manufactured to standards EN345-54 and DIN 2 3329.

■ **Safety Test results**

The boot has been tested under strict conditions as shown in the table.

Nozzle Used	Size	Pressure	Distance	Traversing Speed	Reaction F
Round Jet Nozzle	1.2mm	800 bar	100 mm	0.5 m/s	150N
Round Jet Nozzle	1.5mm	800 bar	100 mm	0.5 m/s	235N
Round Jet Nozzle	1.8mm	800 bar	100 mm	0.5 m/s	250N
Fan Jet Nozzle	1.8mm	800 bar	100 mm	0.5 m/s	240N

The use of different pump flowrates, pressures, stand-off distances and traverse speed can significantly alter the level of protection the boots can offer. The material used offers good resistance to penetration against a water jet, but cannot offer guaranteed protection.



Shoe Size	Stock No.
7 – 7½	tbc
8 – 8½	81600594
9 – 9½	81600592
10 – 10½	81600595
11 – 11½	81600596
12 – 12½	81600596

Please contact us for pricing and availability:

Tel: +44 (0) 1677 424542 - sales@hydroblast.co.uk

or visit our website: www.hydroblast.co.uk