

Hydroblast Part Number: HYBUHPW40



BAR 2700

PSI 40,000



Product Highlight

Key Features	High chemical and abrasion resistance NBR rubber for maximum chemical protection Oil-, chemical-, and slip-resistant NBR sole
Technology	None
Safety standards	CSA Z195-14 / ASTM F2413-11 Grade 1 Steel toe and plate CSA Omega - Electric Shock Resistant 18kV ASTM Mt/75 Metatarsal protection European Standard CE Approved - EN ISO 20345:2011 SRC S5
Ideal	High Pressure Washing Ship Cleaning Bridge Stripping Concrete Cleaning Construction Sites

PRODUCT DESCRIPTION

- High chemical and abrasion resistance
- NBR rubber for maximum chemical protection
- Oil-, chemical-, and slip-resistant NBR sole
- Reinforced backstay for heel/tendon protection
- Steel shank and air cushioned sole pockets
- Adjustable nylon guard keeps out water and debris
- AMC socks (VF22) included
- Air moisture control socket for comfort
- Heavy-duty cotton canvas lining
- Ultra flexible: Exceeds 305,000 Flex Rating

Information and pictures included in this document are credited to Viking.



URS CERTIFICATE NO. 27273



URS CERTIFICATE NO. 27273



URS CERTIFICATE NO. 27273

