

## HOT BOX Series



Inlet and Outlet  
½" BSPP

LED display and  
working hours

Control  
panel

Magnets for easy  
side access

Stainless steel  
fuel cap

Model	HOT BOX 230VAC - 500
<b>Technical Spec.</b> W.P. bar/psi Flow: LPM/GPM Heat energy: kcal/h / kW	500 / 7250 45 / 11.9 90000 / 105
<b>Electrical Spec.</b> Voltage: V Amperage A	230 (50Hz) 2.36
<b>Heat transfer</b> Temp. Increase at 10LPM: °C / °F Temp. Increase at 20LPM: °C / °F Temp. Increase at 30LPM: °C / °F Temp. Increase at 40LPM: °C / °F Temp. Increase at 45LPM: °C / °F	150 / 302 75 / 167 50 / 122 37 / 98.6 33 / 91.4
<b>Packing dimensions</b> L x W x H [mm]	800 x 600 x 1045
<b>Total Packing Weight: Kg / lbs</b>	150 / 330

### Standard accessories incl. with each machine:

- Display showing working hours.
- LED display to show faults and power state.
- Emergency stop button.
- ½" BSPP Inlet and Outlet.
- Magnetically mounted stainless steel side plates, for easy access.
- 4.5 meter cable for power supply.
- 30L robust diesel tank with stainless steel fuel cap.

## Hot Box Set-up



Lifting hot box



HOT BOX with CE20-500 and dry shut gun 500bar



Rotating nozzle



CE 20 Series



CE 40 Series



Safety helmet complete

### Company Profile:

Hydroblast's experience in the high pressure water jetting industry has enabled us to gain access to a range of water jetting pumps and accessories, suitable for numerous applications in the industrial and marine industries.

Hydroblast can supply complete packages to end-users as well as bare shaft pumps and parts. Our main goal is to supply quality products at a competitive price level.